## **TEA ROLLER FOR BLACK TEA**



for Black tea



- Pressurizing board, meticulous pressure control can be selected from original pressurization method by an air cylinder.
- Pressurization is controlled in 10 process & 5 steps by a specific control panel.
- Urges oxygen reaction by loosening tea leaves, with & without pressure repeating alternately, to break the tea leaves' cells and squeeze out the components including oxidases.
- Upper part of the gatepost is removable structure and eazy for cleaning inside pressurizing board and pot.

## Specifications

Туре	Width	Depth	Height	Power	Rotational speed	Cylinder pressure	Input amount (reference)
	mm	mm	mm	kW	rpm	N	kg
BJ-60	2,050	1,690	2,480	2.2	33~49	0~1,000	20~35 (fresh leaf 35~60)
BJ-120	2,430	2,040	2,980	3.7	27~40	0~1,600	40~70 (fresh leaf 70~120)
BJ-200	2,720	2,380	3,440	5.5	23~34	0~2,500	70~120 (fresh leaf 120~200)
BJ-250	3,080	2,650	3,500	7.5	20~30	0~3,000	90~150 (fresh leaf 150~250)

\*Part of the specifications might be changed for improvement.

## 

No.869-1 Ushio Shimada-shi Shizuoka-ken 428-8502 Japan Phone: +81-547-45-5111 Fax: +81-547-45-5110

http://www.web-terada.jp E-mail:info@web-terada.jp

TR133F-03

Sales agent