

# Input screw conveyor

Can be used for multi-purpose since the hopper and transporting unit is concluded individually.



## Features

- Transporting unit is washable with all stainless frame.
- Cleaning is easy since the screw shaft is removable.
- Hopper & transporting unit is connected and relocation is possible easily according to the purpose.
- Fixed amount supplying is possible since it is screw type.

## Optional

- Control panel with inverter (Supplying amount adjusting is possible)
- Vibrating motor (Can be attached to the hopper to prevent piling up)
- Magnet of exit (For metal removing)



## Specifications (as reference)

Type	Conveyor lifting	Hopper volume	Angle	Power		Conveying capacity (Normal finished sencha)
	mm	ℓ		V	kW	kg/h
SCI	1,600	30	60	200 (3 phase)	0.4(1:10)	~200

Remarks: Transfer test is needed when ordering. Conveying ability differs according to the material.

※Part of the specifications might be changed for improvement.

**TERADA** 株式会社 寺田製作所  
TERADA SEISAKUSHO CO.,LTD.

No.869-1 Ushio Shimada-shi Shizuoka-ken 428-8502 Japan  
Phone : +81-547-45-5111 Fax : +81-547-45-5110  
<https://www.web-terada.jp> E-mail: [info@web-terada.jp](mailto:info@web-terada.jp)

● Sales agent

